


PORTABLE LINE

DIESEL

ELECTRIC START ENGINE
3000 r.p.m.



YANMAR



3000
RPM



LWA
2000/14/CE

NOISE
level



AIR
cooled



DIESEL

AVR

AUTOMATIC
VOLTAGE
REGULATOR



SINGLE phase



SINGLE phase



THREE phase



THREE phase

	MGTP 4,5 Y DM AE	MGTP 6,5 Y DM AE	MGTP 7 Y DT AE AVR	MGTP 7 Y DT AE
Code	PP70-4M00	PP71-7M00	PP73-7T00	PP72-7T00
On board control panel equipped with:				
	- Hour counter - Volt meter - Main circuit breaker - 1x16A 1ph 230V EEC socket - 1x16A 1ph 230V Schucko socket	- Hour counter - Volt meter - Main circuit breaker - 1x32A 1ph 230V EEC socket - 1x16A 1ph 230V EEC socket	- Hour counter - Volt meter - Main circuit breaker - 1x32A 3ph 400V EEC socket - 1x16A 1ph 230V EEC socket	- Hour counter - Volt meter - Main circuit breaker - 1x32A 3ph 400V EEC socket - 1x16A 1ph 230V EEC socket
Generator				
Type	Linz E1C10S F	Linz E1C10M H	Linz E1S10MIKE	Linz E1S10M H
Power	4,5 kVA 230V	6,5 kVA 230V	7 kVA 400V	7 kVA 400V
Frequency	50 Hz	50 Hz	50 Hz	50 Hz
Engine				
Engine type	YANMAR L70 AE	YANMAR L100 AE	YANMAR L100 AE	YANMAR L100 AE
N° cylinders	1	1	1	1
Power	6,7 HP	10 HP	10 HP	10 HP
Engine speed	3000 r.p.m.	3000 r.p.m.	3000 r.p.m.	3000 r.p.m.
Cooling	Air	Air	Air	Air
Fuel	Diesel	Diesel	Diesel	Diesel
Starting system	Electric	Electric	Electric	Electric
Dimensions & weight				
Fuel tank capacity	3,5 lt	6 lt	5,4 lt	5,4 lt
Running Time	3,5 h	3,5h	3,5 h	3,5h
Dry weight	100 Kg	120 Kg	122 Kg	122 Kg
Dimensions (L. x W. x H.)	760 x 520 x 690 mm	760 x 520 x 690 mm	760 x 520 x 690 mm	760 x 520 x 690 mm

OPTIONS

☐ Trolley

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.