or your needs

Designed to provide an exceptional level

of performance for every work on site ensuring the right balance between power

and ease of use

TKS-40

T-ZEROPRO

Stainless

steel crown

with 24 nozzles

30-40m

ZERO emissions

100% Electric engine

WORK in safety

fan diameter 900mm





Generator required



TKS-40

central

ZEROPRO

lifting eye



more sustainable and environmentally friendly future



WATER NEBULIZER



APPLICATIONS









Recycling

FEATURES


- Integrated control panel
- SMART START SYSTEM
- Emergency stop button
- Phase inverter
- 1 Water pump 2.2 kW
- 2 Self priming pump for external connection tank 0,05 kW (each)
- Water pressure Gauge
- Water Safety pressure switch
- Manual water drain system
- Central lifting eye
- Forklift pockets
- Stainless steel crown with 24 nozzles
- 3 height adjustable stabilizers
- Equipped with big size wheels for off-road site

OPTIONS

- 60Hz version / 380/480V
- Inlet plug 32A-110V 50Hz
- Road Tow trailer



30-40m water 🌢 nebulizer



Technical data	
Electric engine power (kW)	7,5
Inlet plug	400V3P+N+T 50Hz 32A
Fan diameter (mm)	900
Water consumption (I/m)	37 - 43
Coverage (m)	30 - 40
Water connection	UNI 45 or STORZ or CAMLOCK
Max. water throw height (m)	10
Min. inlet Water pressure (bar)	1.0
Generator required (kVA)	15
Water inlet filter (Mesh)	60
Y Filter (µm)	500
Electric tilting system	0 - 35°
Automatic oscillation (working angle settable manualy)	0 - 340° manual area setting
Dimensions min (mm)	2077x1836x2230
Dimensions max (mm)	2877x1836x2230
Weight (kg)	800



programmable function"cicle" to start electricmotor-water pump oscillation with only one button



Automatic oscillation 0 - 340° manual area setting



Electric Tilting System



SAFETY

Reduce dust for healty and safe environment

Safety automatic clutch compliant with HSE norm

Remote control with full operation

- start/stop
- tilt up/down
- turn left/right/auto