designed and created for your needs

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

TRIME*

TKS-50

TKS-50

T-ZEROPRO

more sustainable and environmentally friendly future

40-50m water onebulizer

ZERO emissions

100% Electric engine powered









20kVA

Generator required





KS-50

T-ZEROPRO



APPLICATIONS









FEATURES


- Integrated control panel
- SMART START SYSTEM
- Emergency stop button
- Phase inverter
- 1 Water pump 2.2 kW
- 2 Self priming pump for external connection tank 0,05 kW (each)
- Water pressure Gauge
- Water Safety pressure switch
- Manual water drain system
- Central lifting eye
- Forklift pockets
- Stainless steel crown with 24 nozzles
- 3 height adjustable stabilizers
- Equipped with big size wheels for off-road site

OPTIONS

- 60Hz version / 380/480V
- Inlet plug 32A-110V 50Hz
- Road Tow trailer



40-50m



Technical data	
Electric engine power (kW)	15
Inlet plug	400V3P+N+T 50Hz 32A
Fan diameter (mm)	900
Water consumption (I/m)	37 - 43
Coverage (without wind)(m)	40 - 50
Water connection	UNI 45 or STORZ or CAMLOCK
Max. water throw height (m)	15
Min. inlet Water pressure (bar)	1.0
Generator required (kVA)	20
Water inlet filter (Mesh)	60
Y Filter (µm)	500
Electric tilting system	0 - 35°
Automatic oscillation	0 - 340°
Dimensions min (mm)	2077x1836x2230
Dimensions max (mm)	2877x1836x2230
Weight (kg)	840



Remote control, 50m range programmable function "cicle" to start electricmotor-water pump oscillation with only one button



Automatic manual area setting



Electric Tilting System



Reduce dust for healty and safe environment

Safety automatic clutch compliant with HSE norm

Remote control with full operation

- start/stop
- tilt up/down
- turn left/right/auto

