or your needs

50-60M

ZERO emissions

100% Electric engine powered







Generator required

fan diameter 900mm central Stainless lifting eye

TRIME

TKS-60

steel crown

with 24 nozzles

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

TKS-60

T-ZEROPRO

more sustainable and environmentally friendly future



TKS-60

T-ZEROPRO



APPLICATIONS









Mining operation

Recycling

FEATURES


- Integrated control panel
- Emergency stop button
- Phase inverter
- 1 Water pump 2.2 kW
- 2 Self priming pump for external connection tank 0,05 kW (each)
- Water pressure Gauge
- Water Safety pressure switch
- Manual water drain system
- Central lifting eye
- Forklift pockets
- Stainless steel crown with 24 nozzles
- 3 height adjustable stabilizers
- Equipped with big size wheels for off-road site

OPTIONS

- 60Hz version / 380/480V
- Road Tow trailer



50-60**m** water 🌢



	Technical data	
)	Electric engine power (kW)	22
	Inlet plug	400V3P+N+T 50Hz 32A
	Fan diameter (mm)	900
	Water consumption (I/m)	37 - 43
	Coverage (without wind) (m)	50 - 60
	Water connection	UNI 45 or STORZ or CAMLOCK
	Max. water throw height (m)	20
	Min. inlet Water pressure (bar)	1.0
	Generator required (kVA)	30
	Water inlet filter (Mesh)	60
	Υ Filter (μm)	500
	Electric tilting system	0 - 35°
	Automatic oscillation	0 - 340°
	Dimensions min (mm)	2077x1836x2230
	Dimensions max (mm)	2877x1836x2230
	Weight (kg)	920



Remote control, 50m range programmable function"cicle" to start electricmotor-water pump oscillation with only one button



Automatic manual area setting



Electric Tilting System



Reduce dust for healty and safe environment

Safety automatic clutch compliant with HSE norm

Remote control with full operation

- start/stop
- tilt up/down
- turn left/right/auto

