

HYBRID LINE

**power  
and innovation**

**STAGE 5  
CERTIFIED**

**39 kVA**  
combined power

**5h run time**

**remote  
telemetry**



**designed and created  
for your needs**

Designed to provide  
an exceptional level  
of performance  
for every work on site  
ensuring the right  
balance between power  
and ease of use

**MGTP  
24000/30TH**



**more sustainable  
and environmentally  
friendly future**

**TRIME®**  
Power Division

# MGTP 24000/30 TH



**REDUCTION**  
emissions **CO<sub>2</sub>**

## APPLICATIONS



Constructions



Road works



Films set



Events

## FEATURES

- ✓ MRS 16 controller
- ✓ 5" Touch monitoring display controller
- ✓ Communication-centre device
- ✓ 48V/1000A BMS to protect the batteries
- ✓ 4G/GPS Antenna + Modem
- ✓ **Remote telemetry & management**
- ✓ Auto recharge of the batteries
- ✓ Automatic peak shaving mode
- ✓ Sides forklift pockets & Central lifting hook
- ✓ Lockable control panel
- ✓ Main circuit breaker & Earth leakage relay
- ✓ Emergency Stop button
- ✓ Bunded tank
- ✓ 3-way valve for external tank
- ✓ Battery switch

## HYBRID LINE

Code	RP314-24TS7
<b>Dimensions</b>	
L x W x H (mm)	2441x1131x1920
Weight (Kg)	1710
<b>Technical Data</b>	
Continuous power (VA)	24000
Battery pack capacity (Wh)	31130
Capacity available DOD 80% (Wh)	24904
Voltage (V)	230/400
Frequency (Hz)	50
<b>Inverter</b>	
Nominal power (VA)	8000
Q.ty	3
System voltage (V)	48
Max charging current (A)	110
<b>Batteries</b>	
Type	LiFePO4
Q.ty	4
Nominal Voltage (V)	25,6
Nominal Capacity (Ah)	304
Cycle Life DOD 80%	>4000
<b>Engine</b>	
Brand	Yanmar
Model	4TNV88
Speed	1500
Cooling system	Water
Emission	Stage V
Fuel Tank (l)	250
<b>Alternator</b>	
Brand	Linz
Model	PRO 18M E/4
Rated output (kVA)	42
Frequency (Hz)	50
Power factor (cos φ)	0,8
<b>Distribution panel</b>	
Inlet Plug	1x 63A-400V
	1x 63A-400V
Outlet Sockets	1x 32A-400V
	1x 16A-230V
<b>Performances</b>	
Running time on batteries (h) 25% load	5,0
Running time on batteries (h) 50% load	2,5
Running time on batteries (h) 75% load	1,5
Recharge time from engine (h)	3
<b>Available options</b>	
RSV 32A plug + MPPT solar charger for external solar panels	
Mat heating system for batteries to work in cold ambients	
OptionGen PRO controller c/w remote check & management and CO2-Fuel savings calculator	

**hybrid**  
technology



**easy handling & transportability**



**TRIME®**

Sales Dept. +39 0382 406 252 - [www.trime.it](http://www.trime.it) - [info@trime.it](mailto:info@trime.it)

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.