

INDUSTRIAL LINE

**power**  
**and innovation**

**360 L**  
**Fuel Tank**  
**capacity**

**designed and created**  
**for your needs**

Designed to provide  
an exceptional level  
of performance  
for every work on site  
ensuring the right  
balance between power  
and ease of use

**MGTP**  
**250 SS-FI**



**more sustainable**  
**and environmentally**  
**friendly future**

 **TRIME**<sup>®</sup>  
Power Division

# MGTP 250 SS-FI

GENSET MODEL



## APPLICATIONS



Constructions



Mining operations



Events



Military applications

## FEATURES

- ✓ Hard wires connection protected
- ✓ Electrical panel ComAp AMF25 mounted on board with safety cover
- ✓ Circuit breaker
- ✓ Internal exhaust gas silencer and insulated manifold
- ✓ Engine oil extraction pump and fuel decanter filter
- ✓ 12V Battery with battery switch
- ✓ Bunded tank
- ✓ Lifting hooks and side forklift pockets

### Options factory installed

220V Electric pre-heater

KIT socket TPS01: **1x32A, 1x16A 3Ph  
1x16A 1Ph + 1x16A Schuko**

KIT socket TPS03: **1x63A, 1x32A, 1x16A 3Ph  
1x16A 1Ph + 1x16A Schuko  
125A breaker with adj. earth fault relay**

Kit AMF and ATS panel

Predisposition for quick release fitting for external fuel tank

Oversize fuel tank 800 l



**easy handling & transportability**

Code	IP227-250TS0
Mechanical version Silenced version with galvanized steel sheet and powder-painted canopy, compact base frame, with bunded tank and leak control	
<b>Dimensions</b>	
L x W x H (mm)	3230 x 1140 x 2200
Dray weight (Kg)	2380
<b>Technical Data</b>	
Prime Power (PRP)(kVA)	250
Prime Power (PRP)(kW)	200
Limited Power (LTP)(kVA)	275
Limited Power (LTP)(kW)	220
Rated Power Factor (cos φ)	0.8
Windings	Three phases Series Star
Rated three-phase concatenated Voltage (V)	400
Rated phase-neutral voltage (V)	230
Rated frequency (Hz)	50
Fuel Tank Capacity (l)	360
Fuel type	Diesel
Sound pressure 7 m. (dBA)	70
<b>Fuel Consumption</b>	
Fuel Cons. at 100% (LTP)(l/h)	57,2
Fuel Cons. at 100% (PRP)(l/h)	51,5
Fuel Cons. at 75% (PRP)(l/h)	38,8
Fuel Cons. at 50% (PRP)(l/h)	24,9
<b>General Alternator data</b>	
Alternator brand	MECC ALTE
Alternator model	EC038 2M4 C
PRP Power (kVA)	250
LTP Power (kVA)	275
Winding	Three phases Series Star
Terminals Number	12
IP Protection	23
Electronic regulator	DSR
Precision	± 1.00 %
<b>General Engine data</b>	
Engine brand	FPT IVECO
Engine model	N67TE8P
Cylinders	6
R.P.M.	1500
Cubic capacity	6700
Air intake	Turbo
Standard voltage (Vdc)	24
Sae	3 - 11
BMEP (kPa)	2607
Cooling	Water
Flywheel P.R.P. Power (kW)	216
Flywheel Stand-by Power (kW)	238,2
Electronic regulator	Standard
Precision class	G3
Oil quantity (l)	17
EU Stage	Non emission certified



**TRIME®**

Sales Dept. +39 0382 406 252 - [www.trime.it](http://www.trime.it) - [info@trime.it](mailto:info@trime.it)

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.