

ENGINE POWERED

designed and created for your needs

Designed to provide
an exceptional level
of performance
for every work on site
ensuring the right
balance between power
and ease of use

X-ECO
ANTIGLARE


6X150W 48V LED - 8,5M

LED TECHNOLOGY

6600 sqm
Illuminated area



45%
reduce
transport costs



more sustainable
and environmentally
friendly future

 **TRIME**[®]
Lighting Towers

6600 sqm

Illuminated area

RUNNING TIME

110 litres tank
200 h
fuel consumption 0,55 l/h

NOISE

level 65 dB(A) at 7m

very compact dimensions

45%
Reduction in Yard Space

APPLICATIONS



Constructions



Mining operations



Emergency



Events



Military applications

FEATURES

- ✓ Multi-directionally adjustable and tiltable floodlights
- ✓ 6x150W, 48V LED lights
- ✓ 48V power between the generator and the lights
- ✓ 7 sections hydraulic vertical tower 8,5 m, 340° rotatable
- ✓ Galvanized metalworks
- ✓ 80 µm powder coating
- ✓ **Very compact dimensions, up to 14 units per truck**
- ✓ Central lifting eye, longitudinal and transversal forklift pockets for effective handling
- ✓ Plug & play, colour coded cables and connectors
- ✓ IP67 level protection certified
- ✓ Guided main coiled cable to avoid damage during tower operation
- ✓ Digital control panel and fuel level indicator
- ✓ Circuit breaker for electrical protection against overload
- ✓ External emergency stop button
- ✓ **Fully bunded tank, 110%**
- ✓ Certified wind stability up to 110 km/h
- ✓ 4 height adjustable stabilizers
- ✓ On board levels for guidance during stabilization
- ✓ **Amoss safety break**



Dimensions & weight

Dimensions min (mm)	2540x1390x2515 (LxWxH)
Dimensions max (mm)	2540x1550x8500 (LxWxH)
Total weight (kg)	920

Floodlights

Type	Led
Power (each)	150W
Floodlights number	6
Illuminated area (sqm)	6600

Mast

Lifting method	Hydraulic
Max Height	8,5 m
Rotation	340°
Max Wind Speed	110 km/h

Alternator

Model	Synchronous
Frequency (Hz)	50
Insulation class	H
Degree of protection	IP 23
Single phase voltage	3,5kVA - 230V
Auxiliary outlets	1,2 kVA

Engine

Model	Kubota Z482*
Fuel	Diesel
r.p.m.	1500
Tank capacity (l)	110
Consumption (l/h)	0,55
Running time	200 h
Noise level dB(A) at 7m	65

* May vary based on stock availability. However, Yanmar primary equivalent brand eventually will be used

X-ECO vs Standard	Standard lighting tower	X-ECO lighting tower	Monthly Savings when using X-ECO light tower
Fuel usage	1,93 l/h	0,55 l/h	1.38 l/h
Fuel costs per month	€ 550,00	€ 150,00	€ 400,00
CO2 Emission month	1.224 kg	336 kg	888 kg
Run time on fuel tank	60 h	200 h	140 h
Lamp type	Metal halide	Led	-
Light sensor	Optional	Standard	-
Amoss kit	Optional	Standard	-



14 units per truck

Safe packaging and loading
allowing quick unloading



easy handling & transportability



TRIME®

Sales Dept. +39 0382 406 252 - www.trime.it - info@trime.it

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.